

# Technical data sheet

## Bauder spray gun & nozzle for use with canisters

V3 08.05.2024

<b>Product description</b>	Spray gun with nozzle connect to the Bauder braided hose to enable the application of canister products. Supplied with 1 nozzle to ensure correct spray pattern. A gauge at the rear of the gun dictates the pressure of the spray.
<b>Application fields</b>	For use with Bauder canister adhesives & primers.
<b>Article Number</b>	GB60300510 (Spray Gun) & GB60300520 (Nozzle)



Characteristic	Unit	Value
Length	mm	627 (inc nozzle)
Colour		silver
Material		stainless steel
Weight	kg	0.728

<b>Storage guidance</b>	The product should be stored dry, protected against weathering, and must not be exposed to temperatures exceeding 35°C. The products must not be exposed to a direct naked flame or other ignition sources, or to solvents or other chemicals. Ensure the product(s) are clear of buildings and any other storage areas. Where there are storage containers on site, these may be suitable for storing products.
<b>Packaging material</b>	All products are despatched in cardboard (readily recyclable) for short term protection.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Disposal guidance</b>	Disposing of any waste material must be carried out in accordance to national regulations. Recommended EWC waste codes:  17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03.
<b>Further information/ documents</b>	Current documents such as brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>

### International Standards Organisation (ISO)

**ISO 9001:2015 Quality Management**  
Certificates EN1271 (UK)

**ISO 14001:2015 Environmental Management Certificates**  
A10552 (UK)

### Installation Guidance

Screw the larger hose nut to the gun thread (clockwise) and tighten with a spanner. Check the hose is securely attached. Remove the safety cap from the canister. Screw the smaller hose nut to the canister (clockwise) and fully tighten with a spanner. Check the hose is securely attached. Turn on the valve on the canister (anti-clockwise). Check connections for any Leaks and if any occur tighten connections. For further details see "Canister Set Up and Maintenance Guide" on the Bauder website.

**Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.**