

Bauder LiquiTOP PVC Primer

safety data sheet According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

Revision date: March 2022 Supersedes : 30.06.2018

COMPANY UNDERTAKING

Bauder Limited
70 Landseer Road
Ipswich
Suffolk IP3 0DH England

W: bauder.co.uk
T: 01473 257671
E: info@bauder.co.uk

1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE

1.1 Product identifier

Product name Bauder LiquiTOP PVC Primer
Article number GB81008140

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised against No specific uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Bauder Limited
70 Landseer Road
Ipswich
Suffolk IP3 0DH England
T: 01473 257671
E: info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only).

For medical advice, members of the public should contact NHS 111

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified
Human health Gas or vapour in high concentrations may irritate the respiratory system.

Physicochemical

The product is highly flammable. Vapours may form explosive mixtures with air.

2.2 Label elements

Pictogram



Signal word **Danger**

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/ attention.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

ACETONE, ETHYL ACETATE, BUTANONE

2.3 Other hazards

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

3.2 Mixtures

ACETONE		30-60%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-0000
Classification		
Flam. Liq. 2 -H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

ETHYL ACETATE			10-30%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01-2119475103-46-0017	
Classification			
Flam. Liq. 2 -H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			

BUTANONE			10-30%
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119475103-46-0017	
Classification			
Flam. Liq. 2 -H225 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Eye Irrit. 2 - H319 STOT SE 3 - H336			

The full text for all hazard statements is displayed in Section 16.

4 FIRST AID MEASURES

4.1 Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5 FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. The product is highly flammable.

Hazardous combustion products Does not decompose when used and stored as recommended.

5.3 Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

Special protective equipment for firefighters Wear chemical protective suit.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4 Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

Storage class Flammable liquid storage.

7.3 Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8 EXPOSURE CONTROL/PERSONAL PROTECTION

8.1 Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

ACETONE (CAS: 67-64-1)

Ingredient comments WEL = Workplace Exposure Limits

ETHYL ACETATE (CAS: 141-78-6)

DNEL Workers - Inhalation; Short term systemic effects: 1468 mg/m³

Workers - Inhalation; Short term local effects: 1468 mg/m³

Consumer - Inhalation; Short term systemic effects: 734 mg/m³

Consumer - Inhalation; Short term local effects: 374 mg/m³

Workers - Inhalation; Long term local effects: 734 mg/m³

Workers - Dermal; Long term systemic effects: 63 mg/kg bw/day

Workers - Inhalation; Long term systemic effects: 734 mg/m³

Consumer - Dermal; Long term systemic effects: 37 mg/kg bw/day

Consumer - Inhalation; Long term systemic effects: 367 mg/m³

Consumer - Oral; Long term systemic effects: 4.5 mg/kg bw/day

Consumer - Inhalation; Long term local effects: 367 mg/m³

- PNEC
- Fresh water; 0.26 mg/l
 - Marine water; 0.026 mg/l
 - Intermittent release; 1.65 mg/l
 - Sediment (Freshwater); 1.25 mg/kg
 - Sediment (Marinewater); 0.125 mg/kg
 - Soil; 0.24 mg/kg
 - STP; 650 mg/l

BUTANONE (CAS: 78-93-3)

Ingredient comments WEL = Workplace Exposure Limits

Biological limit values Short Term Value: 300ppm
Long Term Value: 200ppm

DNEL Consumer - Oral; Long term systemic effects: 31 mg/kg bw/day
Consumer - Dermal; Long term systemic effects: 412 mg/kg bw/day
Workers - Dermal; Long term systemic effects: 1161 mg/kg bw/day
Consumer - Inhalation; Long term systemic effects: 106 mg/m³
Workers - Inhalation; Long term systemic effects: 600 mg/m³

- PNEC
- Fresh water; 55.8 mg/l
 - Sediment (Freshwater); 284.7 mg/kg
 - Intermittent release; 55.8 mg/l
 - Sediment (Marinewater); 284.7
 - Marine water; 55.8 mg/l
 - STP; 709 mg/l
 - Soil; 22.5 mg/kg

8.2 Exposure controls

Protective equipment



Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.
Hygiene measure	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.
Respiratory protection	In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information of basic physical and chemical properties

Appearance	Coloured liquid
Colour	Various colours
Odour	Characteristic
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	500°C @
Flash point	-19°C
Evaporation rate	Not determined.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit, Upper flammable/explosive limit: 1.8-13%
Other flammability	Not available.
Vapour pressure	Not available.

Vapour density	Not available.
Relative density	0.87 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2 Other information

Other information	No information required.
Refractive index	Not available.
Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.

10 STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2 Chemical stability

Stability No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

10.3 Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Not relevant.

10.4 Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5 Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6 Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

11 TOXICOLOGICAL INFORMATION

11.1 Information of toxicological effects

Acute toxicity – oral

ATE oral (mg/kg) 7,462.69

Acute toxicity - dermal

ATE dermal (mg/kg) 7,462.69

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 74.63

Toxicological information on ingredients.

ACETONE

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity – oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,426.0

Species Rat

ATE dermal (mg/kg) 7,426.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 50,100.0

Species Rat

ATE inhalation (vapours mg/l) 50,100.0

Skin corrosion/irritation

Extreme pH Slightly irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

ETHYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 4,100.0

Species Mouse

ATE oral (mg/kg) 4,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 20,000.0

Species Rabbit

ATE dermal (mg/kg) 20,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

BUTANONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 2,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20.0

Species Rat

ATE inhalation (vapours mg/l) 20.0

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Ecological information on ingredients.

ACETONE

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC ₅₀ , 96 hours: 5540 mg/l, Freshwater fish , 96 hours: 11000 mg/l, Marinewater fish LC ₅₀ , 96 hours: 11000 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 8800 mg/l, Daphnia magna EC ₅₀ , 48 hours: 8800 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 430 mg/l, Fish
Acute toxicity – microorganisms	, 30 minutes: 1000 mg/l, Activated sludge

ETHYL ACETATE

Acute toxicity - fish	EC ₅₀ , 48 hours: 610 mg/l, Marinewater fish LC ₅₀ , 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 11.5 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 48 hours: 5600 mg/l, Freshwater algae

BUTANONE

Acute toxicity - fish	LC ₅₀ , EC ₅₀ , IC ₅₀ , : 100 mg/l, Algae
Acute toxicity - aquatic plants	LC ₅₀ , EC ₅₀ , IC ₅₀ , : 100 mg/l, Fish

12.2 Persistence and degradability

Ecological information on ingredients.

ACETONE

Persistence and degradability	The product is expected to be biodegradable.
--------------------------------------	--

12.3 Bioaccumulative potential

Partition coefficient Not available.

Ecological information on ingredients.

ACETONE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

BCF: 3,

Partition coefficient Pow: < -0.24

ETHYL ACETATE

Bioaccumulative potential BCF: 30,

Partition coefficient Not available.

12.4 Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

ACETONE

Mobility The product is miscible with water and may spread in water systems.

Adsorption/desorption coefficient Water - log Koc: 1.5 @ 20°C

Henry's law constant 2929-3070 Pa m³/mol @ 25°C

ETHYL ACETATE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

BUTANONE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

ACETONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

ETHYL ACETATE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

BUTANONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6 Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

ACETONE

Other adverse effects Not applicable.

ETHYL ACETATE

Other adverse effects Not known.

BUTANONE

Other adverse effects None known.

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14 TRANSPORT INFORMATION

14.1 UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

Bauder Limited
70 Landseer Road, Ipswich, IP3 0DH, Suffolk, England
t: +44 (0)1473 257671 w: bauder.co.uk

Bauder Limited
O'Duffy Centre, Carrickmacross, Co Monaghan, Ireland
t: +353 (0)42 9692 333 w: bauder.ie

14.2 UN proper shipping name

Proper shipping name (ADR/RID)	ADHESIVES
Proper shipping name (IMDG)	ADHESIVES
Proper shipping name (ICAO)	ADHESIVES
Proper shipping name (ADN)	ADHESIVES

14.3 transport hazard class(es)

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4 Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

14.5 Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6 Special precautions for user

EmS	F-E, S-D
Emergency Action Code	•3YE
Hazard Identification Number	33 (ADR/RID)
Tunnel restriction code	(D/E)

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

15 REGULATORY INFORMATION

15.1 Safety, health and environment regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2 Chemical safety assessment

No chemical safety assessment has been carried out.

16 OTHER INFORMATION

Issued by	Compliance
Revision date	14.03.2022
Revision	2
Supersedes date	-
Hazard statements in full	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.
Store Between	Store Between 5°C - 25°C
Contains SVHC	NO

Bauder reserves the right to amend information and product specifications without prior notice. All reasonable care has been taken to ensure that all data is current at the time of print, however because Bauder pursues a policy of constant development we recommend ensuring that your copy of this information is current by contacting our Technical Department at technical@bauder.co.uk

Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications, installation techniques and any applicable laws and regulations.