Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en

Replaces version from: 21.09.2018

Print date: 11.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name Bauder LiquiDETAIL S Colour 7031 10kg

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses fluid plastic sealing

Recommended restrictions Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation Bauder Ltd.

> 70 Landseer Road Ipswich IP3 0DH

Telephone: +44 (0)1473 257671

info@bauder.co.uk E-mail (competent person)

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only). For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regula-

tion (EC) No. 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram



GHS02



GHS07

Signal word Danger

Hazardous component(s) to be in-

dicated on label

methyl methacrylate, 2-ethylhexyl acrylate, Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

H225: Highly flammable liquid and vapour. H-statement(s)

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en

BAUDER making roofs secure

Replaces version from: 21.09.2018 Print date: 11.03.2022

H335: May cause respiratory irritation.

* P-statement(s) P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P312: Call a POISON CENTER/doctor if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization Mixture with reactive acrylates

Hazardous ingredients

Ingredient	Numbers	Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	15.0 - 20.0 % by weight
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7REACH No.: 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	10.0 - 15.0 % by weight
aliphatic urethanacrylate		Skin Irrit. 2; H315 Eye Irrit. 2; H319	5.0 - 10.0 % by weight
Fatty acids, C18-un- satd., dimers reaction products with N,N-di- methyl-1,3-propanedi- amine and 1,3-propanedi- amine	CAS No.: 162627-17-0 EC-No.: 605-296-0REACH No.: 01-2119970640-38-XXXX	Skin Sens. 1A; H317	0.1 - 1.0 % by weight
1,1`-(p-Tolylimi- no)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Move out of dangerous area. Take off all contaminated clothing

immediately. Do not leave the victim unattended. Show this safety data sheet

to the doctor in attendance.

If inhaled Move to fresh air. If symptoms persist, call a physician. Show this safety data

sheet to the doctor in attendance.

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en

BHUDEK making roofs secur

Replaces version from: 21.09.2018
Print date: 11.03.2022

In case of skin contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation occurs, seek medical

advice/attention.

In case of eye contact
In the case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

If swallowed Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), Foam, Water spray, Dry powder

Extinguishing media which mustnot

be used for safety reasons

High volume water jet

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature and direct sunlight.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Special protective equipment for

firefighting

Fire residues and contaminated fire extinguishing water must be dis-posed of in accordance with local regulations. Do not allow run-off from fire fighting to

Additional information on fire-

fighting

enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment.

Ensure adequate ventilation. Vapours are heavier than air and mayspread

along floors.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water

or sanitary sewer system. Avoid subsoil penetration.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Clean contaminated surface thoroughly.

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

6.5 Additional information

Other information Treat recovered material as described in the section "Disposal considerations".

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Handle and open container with care. Avoid contact with skin and eyes.

Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty

container away from heat and sources of ignition.

Precautions Smoking, eating and drinking should be prohibited in the application area.

For personal protection see section 8. Observe label precautions.

Advice on protection against fireand

explosion

Take precautionary measures against static discharges. Vapours may form

explosive mixture with air. Use water spray to cool unopened containers.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Keep in properly labelled containers. Containers which are opened mustbe

carefully resealed and kept upright to prevent leakage.

Store in accordance with the particular national regulations. Keep in acool,

well-ventilated place.

TRGS 510

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

methyl methacrylate

monly monday are				
Great Britain				
Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Source
50	208	100	416	EH40/2005 Workplace exposure limits (2011)

Europe			
Long-term exposure value/	Short-term exposure	Issuing date	Source
ppm	value / ppm		
50	100	2009/161	DIRECTIVE 2009/161/EU

DNEL	Target group	Exposure route	Exposure frequency	Source
210 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
210 mg/m ³	Workers		Long term effects systemic	Company data
1,5 mg/cm ²	Workers	Skin	Long term effects Local	Company data

Article-No.: GB81002040



eplaces version from: 21.09.2018 Print date: 11.03.2022

Revision Date: 11.03.2022	Re
Version: 2.0/en	

13,67 mg/kg	Workers	Skin	Long term effects systemic	Company data
105 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data
74,3 mg/m³	Consumers	Inhalation	Long term effects, systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Long term effects Local	Company data
8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

2-ethylhexyl acrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Short term effects Local	Company data
4,5 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data

PNEC	Exposure route	Source
0,002752 mg/l	fresh water	Company data
0,000272 mg/l	seawater	Company data
2,3 mg/l	wastewater treatment plant	Company data
0,126 mg/kg	sediment Water	Company data
0,126 mg/kg	sediment seawater	Company data
1,0 mg/kg	Soil	Company data
0,0023 mg/kg	Intermittent release.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC	Exposure route	Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

8.2 Exposure controls

Respiratory protection Use the indicated respiratory protection if the occupational exposure limit is

exceeded and/or in case of product release (dust).

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en

BAUDER

Replaces version from: 21.09.2018
Print date: 11.03.2022

Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposurelimit they

must use appropriate certified respirators.

Remarks Recommended Filter type: A1, A2 (in case of higher concentration)

Hand protection Protective gloves complying with EN 374.Please observe the instructions

regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Unsuitable material woven fabric, Leather gloves

Suitable material Nitrile

Eye protection Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment. Long sleeved clothing

General protective and hygiene

measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday. Use protective skin cream be-fore handling the

product. Avoid contact with the skin and the eyes.

Engineering measures Ensure adequate ventilation, especially in confined areas. When workers

are facing concentrations above the exposure limit they must use appropriate

certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Form Liquid

Colour different color-tone
Odour typic for acrylates

Boiling point [°C] >100 °C
Flash point [°C] 10 °C

Evaporation rate [kg/(s m²)] not determined

Explosion limits [Vol-%] methyl methacrylate

Lower limit 1,7 vol. %

Upper limit 12,5 vol. %

2-ethylhexyl acrylate

Lower limit 0,9 vol. % Upper limit 6,4 vol. %

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en

Replaces version from: 21.09.2018

Print date: 11.03.2022

Remarks The product itself has not been tested.

Vapour density not determined

Density [g/cm³] 1,33 g/cm3

Water solubility [g/l]

insoluble Remarks

Partition coefficient n-octanol /water

not determined

(log P O/W)

Autoignition temperature [°C] not determined 40000 mPa.s Viscosity, dynamic [kg/(m s)]

> Temperature [°C] 20°C

Measuring method Haake-Viscotester

Explosive properties Not relevant

In use, may form flammable/explosive vapour-air mixture.

Oxidising properties Not relevant

9.2 Other information

Ignition temperature [°C] 280 °C

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions The product is normally supplied in a stabilized form. If the permissible

storage period and/or storage temperature is noticeably exceeded, the product may

polymerize with heat evolution. Risk of receptacle bursting.

10.4 Conditions to avoid

Conditions to avoid Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid Reacts violently with peroxides. Reducing agents, Strong bases, Amines,

Oxidizing agents

SECTION 11: Toxicological information

11.1 Information on toxicological effects

*Oral toxicity [mg/kg]

*methyl methac	rylate			
Value	Test criterion	Test species	Measuring	Source
			method	

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

>5001 mg/kg	LD50	rat	OECD Test	Company data
			Guideline 401	

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
4435 mg/kg	LD50	rat	Company data

aliphatic urethanacrylate			
Value	Test criterion	Test species	Source
>2001 mg/kg	LD50	rat	Company data

_	Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine				
Value	Test criterion	Test species	Measuring method	Source	
>10000 mg/kg	LD50	rat	OECD Test Guideline 401	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Measuring	Source
			method	
26 mg/kg	LD50	rat	OECD Test	Company data
			Guideline 423	

*Dermal toxicity [mg/kg]

Hazardous ingredients

*methyl methacrylate			
Value	Test criterion	Test species	Source
>5001 mg/kg	LD50	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol			
Value	Test criterion	Test species	Source
2001 mg/kg	LD50	rat	Company data

*Inhalative toxicity [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate		
Value	Test species	Source
1,19 mg/l	rat	Company data

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

methyl methacrylate

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018

Print date: 11.03.2022	

Value	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	Company data

*Irritant effect on skin

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
irritating	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test species	Exposure duration	Source
		[h]	
Skin irritation	rabbit	4 h	Company data

aliphatic urethanacrylate	
Value	Source
May cause skin irritation.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine			
Value	Measuring method	Test species	Source
No skin irritation	OECD Test Guideline 404	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No skin irritation	Company data

*Irritant effect on eyes

methyl methacrylate		
Value	Test species	Source
Irritant	rabbit	Company data

2-ethylhexyl acrylate			
Value	Measuring method	Test species	Source
slightly irritating	OECD Test Guideline 405	rabbit	Company data

aliphatic urethanacrylate	
Value	Source
Causes serious eye irritation.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-			
propanediamine			
Value Measuring method Test species Source			

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

No eye irritation	OECD Test Guideline 405	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Irritant	Company data

*Sensitization

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Skin sensitization	mouse	Company data

2-ethylhexyl acrylate	
Value	Source
Skin sensitization	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine		
Value	Measuring method	Source
Skin sensitizer	OECD 429	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No sensitization responses were observed.	Company data

Carcinogenic effects

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
not a carcinogen	rat, mouse	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Mutagenicity

methyl methacrylate	
Value	Source
not mutagenic	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine		
Value	Measuring method	Source
negative	Ames test OECD 471	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
negative	Company data

*Reproduction toxicity

Hazardous ingredients

methyl methacrylate	
Value	Source
not toxic to reproduction	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
Causes respiratory tract irritation.	Company data

2-ethylhexyl acrylate	
Value	Source
Causes respiratory tract irritation.	Company data

*Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
No known effect.	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritating to mucous membranes

Article-No.: GB81002040

Replaces version from: 21.09.2018 Print date: 11.03.2022

Revision Date: 11.03.2022 Version: 2.0/en

SECTION 12: Ecological information

12.1 Toxicity

*Toxicity to fish [mg/l]

Hazardous ingredients

methyl metl	methyl methacrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
191 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

2-ethylhexy	2-ethylhexyl acrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
1,81 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine					
Value	Test criterion	Test species	Measuring method	Source	
>150 mg/l	LC50	Leuciscus idus (Golden orfe)	DIN 38412	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol							
Value	Test criterion	Test species	Exposure duration [h]	Source			
17 mg/l	LC50	Brachydanio rerio (zebra fish)	96 h	Company data			

*Toxicity to daphnia [mg/l]

methyl methacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
69 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data

2-ethylhexyl acrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,3 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

aliphatic urethanacrylate						
Value	Test criterion	Test species	Source			
>100 mg/l	LC50	Daphnia magna (Water flea)	Company data			

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
>101 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data

1,1`-(p-Tolylimino)dipropan-2-ol							
Value	Test criterion	Test species	Exposure duration [h]	Source			
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data			

*Toxicity to algae [mg/l]

methyl meth	methyl methacrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
>110 mg/l	EC50	Selenastrum capricornu- tum (green algae)	72 h	OECD Test Guideline201	Company data		

2-ethylhexyl	2-ethylhexyl acrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,71 mg/l	ErC50	Desmod- esmus sub- spicatus	72 h	OECD Test Guideline201	Company data	

- ,	Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine				
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
>101 mg/l	ErC50	Pseudokirch- neriella sub- capitata	72 h	OECD Test Guideline201	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure duration [h]	Source
245 mg/l	EC50	Desmodesmus subspicatus	27 h	Company data

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

NOEC (fish) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (ze- bra fish)	OECD Test Guideline 210	Company data
	Dra norry	210	

NOEC (daphnia) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

NOEC (algae) [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate			
Value	Test species	Measuring method	Source
0,45 mg/l	Desmodesmus subspicatus	OECD Test Guideline 201	Company data

12.2 Persistence and degradability

*Biodegradability

Hazardous ingredients

methyl methacrylate		
Value	Method of analysis	Source
Readily biodegradable.	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	Company data

2-ethylhexyl acrylate	
Value	Source
Readily biodegradable.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine			
Value Measuring method Source			
Not readily biodegradable. OECD 301 Company data			

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Poorly biodegradable.	Company data

12.3 Bioaccumulative potential

*Bioaccumulation

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

Hazardous ingredients

methyl methacrylate	
Value	Source
Does not bioaccumulate.	Company data

2-ethylhexyl acrylate	
Value	Source
Bioaccumulation slight, log Pow 4,64	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
no data available	Company data

12.4 Mobility in soil

Mobility

Hazardous ingredients

methyl methacrylate	
Mobility	Source
Terrestrial Compartment Not relevant	Company data

12.5 Results of PBT and vPvB assessment

*Results of PBT characteristics determination

	methyl methacrylate		
ı	Value	Source	
L	value	Source	
	This substance is not considered to be persistent,	Company data	
	bioaccumulating nor toxic (PBT).		

2-ethylhexyl acrylate		
Value	Source	
This substance is not considered to be persistent,	Company data	
bioaccumulating nor toxic (PBT).		

aliphatic urethanacrylate		
Value	Source	
This substance is not considered to be persistent,	Company data	
bioaccumulating nor toxic (PBT).		

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

12.6 Other adverse effects

Further information on ecology We have no quantitative data concerning the ecological effects of this

product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations According to the European Waste Catalogue, Waste Codes are not product

specific, but application specific. The following Waste Codes are only

suggestions:

Waste Code 08 01 11* waste paint and varnish containing organic solvents or other

dangerous substances

Uncleaned empty packaging Empty containers should be taken for local recycling or waste disposal.

Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the	PAINT	PAINT	PAINT
goods			
UN proper shipping name		PAINT	Paint
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	III	III	III
Labels	3	3	3
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC

Not relevant

Code

Commercial Product Name: Bauder LiquiDETAIL S Colour 7031 10kg

Article-No.: GB81002040 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Additionally, observe any national regulations!

Classification in compliance withthe

Industrial Safety Regulation

highly flammable

GISCODE RMA10 MAL-Code 4-5

SECTION 16: Other information

* Modifications since last version Modifications of the previous version are denoted with an asterisk (*).

Relevant H-phrases H225: Highly flammable liquid and vapour.

H300: Fatal if swallowed. H315: Causes skin irritation.

H317: May cause an allergic skin reaction.H319: Causes serious eye irritation.H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Wording of the hazard classes Flam. Liq.: Flammable liquid

STOT SE: Specific target organ toxicity - single exposure

Skin Irrit.: Skin irritation Skin Sens.: Skin sensitization

Aquatic Chronic: Hazardous to the aquatic environment

Eye Irrit.: Serious eye irritation Acute Tox.: Acute toxicity

* Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Flam. Liq. 2; H225	Calculated
Skin Irrit. 2; H315	Calculated
Skin Sens. 1; H317	Calculated
STOT SE 3; H335	Calculated

Recommended restrictions Reserved for industrial and professional use.

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.