SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name

Bauder LiquiPASTE Colour 7032 15 kg

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	fine sanding surfacer
Recommended restrictions	Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation	Bauder Ltd. 70 Landseer Road
	Ipswich IP3 0DH Telephone: +44 (0)1473 257671
E-mail (competent person)	info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only). For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram




Danger



Signal word

Hazardous component(s) to be indicated on label

H-statement(s)



H225: Highly flammable liquid and vapour. H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en Replaces version from: 21.09.2018 Print date: 14.03.2022

P-statement(s)

H335: May cause respiratory irritation.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P312: Call a POISON CENTER/doctor if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Mixture with reactive acrylates

Hazardous ingredients

Ingredient	Numbers	Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	20.0 - 25.0 % by weight
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7REACH No.: 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	10.0 - 15.0 % by weight
aliphatic urethanacrylate		Skin Irrit. 2; H315 Eye Irrit. 2; H319	5.0 - 10.0 % by weight
Fatty acids, C18-un- satd., dimers reaction products with N,N-di- methyl-1,3-propanedi- amine and 1,3-propanedi- amine	CAS No.: 162627-17-0 EC-No.: 605-296-0REACH No.: 01-2119970640-38-XXXX	Skin Sens. 1A; H317	1.0 - 5.0 % by weight
1,1`-(p-Tolylimi- no)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight
2,2'-ethylenedioxydiethyl dimethacrylate	CAS No.: 109-16-0 EC-No.: 203-652-6REACH No.: 01-2119969287-21-XXXX	Skin Sens. 1; H317	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

BAU making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

If inhaled	Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
In case of skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, seek medical advice/attention.
In case of eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO2), Foam, Water spray, Dry powder
Extinguishing media which mustnot	High volume water jet
be used for safety reasons	

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters	In the event of fire, wear calf contained breathing apparatus
itself, its combustion products, or released gases	
Special exposure hazards arising from the substance or preparation	Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature anddirect sunlight.

In the event of fire, wear self-contained breathing apparatus.

Special protective equipment for	
firefighting	Fire residues and contaminated fire extinguishing water must be dis- posed of
Additional information on fire-	in accordance with local regulations. Do not allow run-off fromfire fighting to
fighting	enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Personal precautions Ensure adequate ventilation. Vapours are heavier than air and mayspread along floors.

6.2 Environmental precautions

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

6.3 Methods and material for containment and cleaning up Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly. 6.5 Additional information Other information Treat recovered material as described in the section "Disposal considerations". SECTION 7: Handling and storage 7.1 Precautions for safe handling Advice on safe handling Handle and open container with care. Avoid contact with skin and eyes. Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty container away from heat and sources of ignition. Precautions Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Observe label precautions. Advice on protection against fireand Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers. explosion 7.2 Conditions for safe storage, including any incompatibilities Storage space and container Keep in properly labelled containers. Containers which are opened mustbe carefully resealed and kept upright to prevent leakage. requirements Store in accordance with the particular national regulations. Keep in acool, well-ventilated place. **TRGS 510** 3 Recommended storage tempera-Keep in a dry, cool place. ture

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

methyl methacrylate

Great Britain				
Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3	
50	208	100	416	EH40/2005 Workplace
				exposure limits (2011)

Europe				
Long-term exposure value/ Short-term exposure value / Issuing date Source				
ppm 50	100	2009/161	DIRECTIVE 2009/161/EU	

Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en Replaces version from: 21.09.2018 Print date: 14.03.2022

DNEL	Target group	Exposure route	Exposure frequency	Source
210 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
210 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
1,5 mg/cm ²	Workers	Skin	Long term effects Local	Company data
13,67 mg/kg	Workers	Skin	Long term effects systemic	Company data
105 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data
74,3 mg/m³	Consumers	Inhalation	Long term effects, systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Long term effects Local	Company data
8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

2-ethylhexyl acrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m ³	Workers	Inhalation	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Short-term effects Local	Company data
4,5 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data

PNEC	Exposure route	Source
0,002752 mg/l	fresh water	Company data
0,000272 mg/l	seawater	Company data
2,3 mg/l	wastewater treatment plant	Company data
0,126 mg/kg	sediment Water	Company data
0,126 mg/kg	sediment seawater	Company data
1,0 mg/kg	Soil	Company data
0,0023 mg/kg	Intermittent release.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m ³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC Exposure route		Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

2,2'-ethylenedioxydiethyl dimethacrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
48,5 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
13,9 mg/kg	Workers	dermal exposure	Long term effects systemic	Company data
14,5 mg/m ³	Consumers	Inhalation	Long term effects systemic	Company data
8,33 mg/kg	Consumers	dermal exposure	Long term effects systemic	Company data
8,33 mg/kg	Consumers	Oral	Long term effects systemic	Company data

PNEC	Exposure route	Source	
0,164 mg/l	freshwater	Company data	
0,274 mg/kg	Soil	Company data	
0,185 mg/kg	marine sediment	Company data	
1,85 mg/kg	freshwater sediment	Company data	
10 mg/l	Waste water treatment	Company data	
0,164 mg/l	intermittent releases	Company data	
0,00164 mg/l	marine water	Company data	

8.2 Exposure controls

Respiratory protection	Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
Remarks	Recommended Filter type: A1, A2 (in case of higher concentration)	
Hand protection	Protective gloves complying with EN 374.Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.	
Unsuitable material	woven fabric, Leather gloves	
Suitable material	Nitrile	
Eye protection	Tightly fitting safety goggles	
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing	
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday. Use protective skin cream be-fore handling the product. Avoid contact with the skin and the eyes.	



Engineering measures

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	Liquid
Colour	grey
Odour	smell of Methylmethacrylate
рН	not applicable
Melting point [°C] / Freezing point[°C]	not determined
Boiling point [°C]	> 100 °C
Flash point [°C]	10 °C
Evaporation rate [kg/(s m ²)]	not determined
Explosion limits [Vol-%]	The product itself has not been tested. methyl methacrylate
Lower limit	1,7 vol. %
Upper limit	12,5 vol. % 2-ethylhexyl acrylate
Lower limit	0,9 vol. %
Upper limit	6,4 powder
Vapour pressure [kPa]	not determined
Vapour density	not determined
Density [g/cm ³]	1,38 g/cm ³
Temperature [°C]	20 °C
Water solubility [g/l]	
Remarks	insoluble
Partition coefficient n-octanol /water (log P O/W)	not determined
Autoignition temperature [°C]	not determined
Viscosity, dynamic [kg/(m s)]	50.000 mPas*s
Temperature [°C]	20 °C

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

Replaces version from: 21.09.2018 Print date: 14.03.2022

Measuring method	Haake-Viscotester
Explosive properties	Not relevant In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	Not relevant
9.2 Other information	
Ignition temperature [°C]	280 °C

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions	The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Risk of receptacle bursting.
10.4 Conditions to avoid	
Conditions to avoid	Extremes of temperature and direct sunlight.
10.5 Incompatible materials	
Materials to avoid	Reacts violently with peroxides. Reducing agents, Strong bases, Amines, Oxidizing agents

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

methyl methacrylate				
Test criterion	Test species	Measuring	Source	
		method		
LD50	rat	OECD Test Guideline 401	Company data	
	Test criterion	Test criterion Test species	Test criterionTest speciesMeasuring methodLD50ratOECD Test	

2-ethylhexyl acrylate				
Value	Test criterion	Test species	Source	
4435 mg/kg	LD50	rat	Company data	

aliphatic urethanacrylate				
Value Test criterion Test species Source				
>2001 mg/kg	LD50	rat	Company data	

• •	Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine				
Value	Value Test criterion Test species Measuring Source method				

Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

BAUDER

>10000 mg/kg LD50 rat	OECD Test Guideline 401	Company data
-----------------------	----------------------------	--------------

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Measuring method	Source
26 mg/kg	LD50	rat	OECD Test Guideline 423	Company data

2,2'-ethylenedioxydiethyl dimethacrylate				
Value	Test criterion	Test species	Remarks	Source
10066 mg/kg	LD50	rat	* 1)	Company data

1): Information given is based on data on the components and the toxicology of similar products.

Dermal toxicity [mg/kg]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
>5001 mg/kg	LD50	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Source	
2001 mg/kg	LD50	rat	Company data	

2,2'-ethylenedioxydiethyl dimethacrylate				
Value	Test criterion	Test species	Source	
>2001 mg/kg	LD50	mouse	Company data	

Inhalative toxicity [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate				
Value	Test species	Source		
1,19 mg/l	rat	Company data		

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	Company data

Irritant effect on skin

Hazardous ingredients

methyl methacrylate

Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

BAUDE

R

Value	Test species	Source
irritating	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test species	Exposure duration [h]	Source
Skin irritation	rabbit	4 h	Company data

aliphatic urethanacrylate	
Value	Source
May cause skin irritation.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine			
Value	Measuring method	Test species	Source
No skin irritation	OECD Test Guideline 404	rabbit	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No skin irritation	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value Source	
No skin irritation	Company data

Irritant effect on eyes

Hazardous ingredients		
methyl methacrylate		
Value	Test species	Source
Irritant	rabbit	Company data

2-ethylhexyl acrylate			
Value	Measuring method	Test species	Source
slightly irritating	OECD Test Guideline 405	rabbit	Company data

aliphatic urethanacrylate	
Value	Source
Causes serious eye irritation.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine			
Value	Measuring method	Test species	Source
No eye irritation	OECD Test Guideline 405	rabbit	Company data



1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Irritant	Company data

2,2'-ethylenedioxydiethyl dimethacrylate		
Value Source		
No eye irritation	Company data	

Sensitization

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Skin sensitization	mouse	Company data

2-ethylhexyl acrylate	
Value	Source
Skin sensitization	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine					
Value Measuring method Source					
Skin sensitizer	OECD 429	Company data			

1,1`-(p-Tolylimino)dipropan-2-ol			
Value Source			
No sensitization responses were observed.	Company data		

2,2'-ethylenedioxydiethyl dimethacrylate			
Value Source			
Skin sensitizer	Company data		

Carcinogenic effects

Hazardous ingredients

methyl methacrylate			
Value	Test species	Source	
not a carcinogen	rat, mouse	Company data	

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate			
Value Source			
No known effect.	Company data		

Mutagenicity

Safety Data Sheet as per regulation (EC) 1907/2006
Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg
Article-No.: GB81004010
Revision Date: 14.03.2022
Version: 2.0/en

Replaces version from: 21.09.2018 Print date: 14.03.2022

Value	Source	
not mutagenic	Company da	ata
2-ethylhexyl acrylate Value	Source	
No known effect.		ata
No known enect.	Company da	ala
Fatty acids, C18-unsatd., dim propanediamine	ers reaction products with N,N-dime	ethyl-1,3-propanediamine and 1,
Value	Measuring method	Source
negative	Ames test OECD 471	Company data
1,1`-(p-Tolylimino)dipropan-2		
Value	Source	
negative	Company da	ata
2,2'-ethylenedioxydiethyl din	nothacrulato	
Z,Z'-ethylenedloxydiethyl din Value	Source	
No known effect.		ata
NO KNOWN Effect.	Company da	ata
	Source	
rdous ingredients methyl methacrylate Value		ata
ardous ingredients methyl methacrylate	Source Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate	Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value	Company da Company da Source	
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate	Company da	
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect.	Company da Company da Source Company da	
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din	Company da Company da Source Company da	
Value not toxic to reproduction 2-ethylhexyl acrylate Value	Company da Source Company da Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. target organ toxicity (single execution)	Company da Company da Source Company da nethacrylate Company da Company da Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients	Company da Company da Source Company da nethacrylate Company da Company da Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. xarget organ toxicity (single example a single example a sino	Company da Company da Source Company da nethacrylate Company da Company da Company da	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients methyl methacrylate Value	Company da Source Company da nethacrylate Company da cposure) [mg/kg] Source Source	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients methyl methacrylate	Company da Company da Source Company da nethacrylate Company da Company da company da secondaria (company da company da c	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients methyl methacrylate Value	Company da Source Company da nethacrylate Company da cposure) [mg/kg] Source Source	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exactly in a single exactly in a sing	Company da Source Company da nethacrylate Company da cposure) [mg/kg] Source Source	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients methyl methacrylate Value Causes respiratory tract irritation. 2-ethylhexyl acrylate	Company da Source Company da nethacrylate Company da co	ata
ardous ingredients methyl methacrylate Value not toxic to reproduction 2-ethylhexyl acrylate Value No known effect. 2,2'-ethylenedioxydiethyl din Value No known effect. arget organ toxicity (single exardous ingredients methyl methacrylate Value Causes respiratory tract irritation. 2-ethylhexyl acrylate Value	Company da Source Company da nethacrylate Company da cposure) [mg/kg] Source Company da Source Company da Source Source	ata

Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
No known effect.	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate			
Value Source			
No known effect.	Company data		

11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritatingto mucous membranes

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

methyl meth	methyl methacrylate					
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source	
191 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data	

2-ethylhexyl	2-ethylhexyl acrylate						
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source		
1,81 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data		

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine					
Value	Test criterion	Test species	Measuring method	Source	
>150 mg/l	LC50	Leuciscus idus (Golden orfe)	DIN 38412	Company data	

Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

BAUDER

1,1`-(p-Tolylimino)dipropan-2-ol							
Value	Test criterion	Test species	Exposure dura- tion [h]	Source			
17 mg/l	LC50	Brachydanio rerio (zebra fish)	96 h	Company data			

2,2'-ethylenedioxydiethyl dimethacrylate					
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source
16,4 mg/l	LC50	Brachydanio rerio (zebra fish)	OECD Test Guideline203	96 h	Company data

Toxicity to daphnia [mg/l]

methyl methacrylate							
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
69 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data		

2-ethylhexyl acrylate							
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
1,3 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data		

aliphatic urethanacrylate					
Value	Test criterion	Test species	Source		
>100 mg/l	LC50	Daphnia magna (Water flea)	Company data		

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
>101 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol						
Value	Test criterion	Test species	Exposure duration [h]	Source		
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data		

making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

BAUDER

2,2'-ethylenedioxydiethyl dimethacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Source	
30,2mg/l	EC50	Daphnia magna (Water flea)	21 day(s)	Company data	

Toxicity to algae [mg/l] Hazardous ingredients

nazaruous ingreulents
mothyl mothacrylato

methyl meth	methyl methacrylate							
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source			
>110 mg/l	EC50	Selenastrum capricornu- tum (green algae)	72 h	OECD Test Guideline201	Company data			

2-ethylhexyl	2-ethylhexyl acrylate						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
1,71 mg/l	ErC50	Desmod- esmus sub- spicatus	72 h	OECD Test Guideline201	Company data		

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine						
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
>101 mg/l	ErC50	Pseudokirch- neriella sub- capitata	72 h	OECD Test Guideline201	Company data	

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure duration [h]	Source	
245 mg/l	EC50	Desmodesmus subspicatus	27 h	Company data	

2,2'-ethylenedioxydiethyl dimethacrylate							
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source		
>101 mg/l	EC50	Pseudokirch- neriella sub- capitata	72 h	OECD Test Guideline201	Company data		

NOEC (fish) [mg/l]

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (zebra fish)	OECD Test Guideline 210	Company data

Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en

making roofs secure. Replaces version from: 21.09.2018 Print date: 14.03.2022

BAU

NOEC (daphnia) [mg/l]

	• • • • • • • • • • • • • • • •
Hazardous	ingredients
i luzui uouo	ingrouionto

methyl methacrylate			
Value	Test species	Measuring method	Source
37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

NOEC (algae) [mg/l]

Hazardous ingredients

2-ethylhexyl acrylate			
Value	Test species	Measuring method	Source
0,45 mg/l	Desmodesmus subspicatus	OECD Test Guideline 201	Company data

12.2 Persistence and degradability

Biodegradability

Η	lazar	dous	ingred	lients

methyl methacrylate		
Value	Method of analysis	Source
Readily biodegradable.	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	Company data

2-ethylhexyl acrylate	
Value	Source
Readily biodegradable.	Company data

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine					
Value	Measuring method	Source			
Not readily biodegradable.	OECD 301	Company data			

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
Poorly biodegradable.	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
Readily biodegradable.	Company data

12.3 Bioaccumulative potential

Bioaccumulation

Hazardous ingredients methyl methacrylate Source Value Source Does not bioaccumulate. Company data



2-ethylhexyl acrylate	
Value	Source
Bioaccumulation slight, log Pow 4,64	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
no data available	Company data

2,2'-ethylenedioxydiethyl dimethacrylate	
Value	Source
slight	Company data

12.4 Mobility in soil

Mobility

Hazardous ingredients	
methyl methacrylate	
Mobility	Source
Terrestrial Compartment Not relevant	Company data

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

methyl methacrylate	
Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

2-ethylhexyl acrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

aliphatic urethanacrylate	
Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

Fatty acids, C18-unsatd., dimers reaction products with N,N-dimethyl-1,3-propanediamine and 1,3- propanediamine	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

Replaces version from: 21.09.2018 Print date: 14.03.2022

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

2,2'-ethylenedioxydiethyl dimethacrylate		
Value	Source	
This substance is not considered to be persistent,	Company data	
bioaccumulating nor toxic (PBT).		

12.6 Other adverse effects

Further information on ecology We have no quantitative data concerning the ecological effects of this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are onlysuggestions:
Waste Code	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Uncleaned empty packaging	Empty containers should be taken for local recycling or waste disposal. Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the goods	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group		111	
Labels	3	3	3
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Bauder LiquiPASTE Colour 7032 15 kg Article-No.: GB81004010 Revision Date: 14.03.2022 Version: 2.0/en



14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC Code Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations	Additionally, observe any national regulations!
Classification in compliance withthe Industrial Safety Regulation	highly flammable
GISCODE	RMA10
MAL-Code	4-5

SECTION 16: Other information

Relevant H-phrases	 H225: Highly flammable liquid and vapo H300: Fatal if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction H319: Causes serious eye irritation. H335: May cause respiratory irritation. H412: Harmful to aquatic life with long lateral 	on.
Wording of the hazard classes	Flam. Liq.: Flammable liquid STOT SE: Specific target organ toxicity - single exposure Skin Irrit.: Skin irritation Skin Sens.: Skin sensitization Aquatic Chronic: Hazardous to the aquatic environment Eye Irrit.: Serious eye irritation Acute Tox.: Acute toxicity	
Classification for mixtures and used	Classification	Evaluation Calculated
evaluation method according to regulation (EC) 1272/2008 [CLP]	Flam. Liq. 2; H225 Skin Irrit. 2; H315	Calculated
	Skin Sens. 1; H317	Calculated

STOT SE 3; H335

Recommended restrictions

Reserved for industrial and professional use.

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.

Calculated