Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

<u>SECTION 1: Identification of the substance/mixture and of the company/undertaking</u>

1.1 Product identifier

Commercial Product Name Bauder LiquiPAVE R SO 10KG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses grout resin

Recommended restrictions Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company designation Bauder Ltd.

70 Landseer Roadlpswich

IP3 0DH

Telephone: +44 (0)1473 257671

E-mail (competent person) info@bauder.co.uk

1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only). For medical advice, members of the public should contact NHS 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regula- Flan

tion (EC) No. 1272/2008

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

2.2 Label elements

Hazard pictogram





GHS07

GHS02

Signal word Danger

Hazardous component(s) to be in-

dicated on label H-statement(s) methyl methacrylate, 2-ethylhexyl acrylate

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H335:

May cause respiratory irritation.

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

P-statement(s) P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. P233: Keep container tightly closed.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P312: Call a POISON CENTER/doctor if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P403+P233: Store in a well-ventilated place. Keep container tightly closed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization Mixture with reactive acrylates

Hazardous ingredients

Ingredient	Numbers	Classification (EC) 1272/2008	Concentration
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6REACH No.: 01-2119452498-28-XXXX	Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1;H317	35.0 - 40.0 % by weight
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7REACH No.: 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	20.0 - 25.0 % by weight
aliphatic urethanacrylate		Skin Irrit. 2; H315 Eye Irrit. 2; H319	5.0 - 10.0 % by weight
1,1`-(p-Tolylimi- no)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1REACH No.: 01-2119980937-17-XXXX	Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	0.1 - 1.0 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Move out of dangerous area. Take off all contaminated clothing immediately.

Do not leave the victim unattended. Show this safety data sheet to the doctor

in attendance.

If inhaled Move to fresh air. If symptoms persist, call a physician. Show this safety data

sheet to the doctor in attendance.

In case of skin contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation occurs, seek medical

advice/attention.

In case of eye contact Bei anhaltenden Beschwerden Augenarzt hinzuziehen.

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en

BHUDEK making roofs secur

Replaces version from: 21.09.2018
Print date: 11.03.2022

In the case of contact with eyes, rinse immediately with plenty of waterand seek

medical advice.

If swallowed Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Feuerlöscher (Pulver, Schaum, CO2)

Carbon dioxide (CO2), Foam, Water spray, Dry powder

Extinguishing media which mustnot

be used for safety reasons

High volume water jet

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Hazardous decomposition products formed under fire conditions. Violent polymerization may be caused by: Extremes of temperature and direct sunlight.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Special protective equipment for

firefighting

Additional information on fire-

fighting

Fire residues and contaminated fire extinguishing water must be dis- posed of in accordance with local regulations. Do not allow run-off fromfire fighting to

enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment.

Ensure adequate ventilation. Vapours are heavier than air and mayspread

along floors.

6.2 Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or

sanitary sewer system. Avoid subsoil penetration.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Clean contaminated surface thoroughly.

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en

BAUDER

Replaces version from: 21.09.2018
Print date: 11.03.2022

6.5 Additional information

Other information Treat recovered material as described in the section "Disposal considerations".

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Handle and open container with care. Avoid contact with skin and eyes.

Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty

container away from heat and sources of ignition.

Precautions Smoking, eating and drinking should be prohibited in the application area.

For personal protection see section 8. Observe label precautions.

Advice on protection against fireand

explosion

Take precautionary measures against static discharges. Vapours may form

explosive mixture with air. Use water spray to cool unopened containers.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Keep in properly labelled containers. Containers which are opened mustbe

carefully resealed and kept upright to prevent leakage.

Store in accordance with the particular national regulations. Keep in acool,

well-ventilated place.

TRGS 510 3

Recommended storage tempera-

recommended storage tempera-

Keep in a dry, cool place.

ture

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

methyl methacrylate

Great Britain						
Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source		
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3			
50	208	100	416	EH40/2005 Workplace		
				exposure limits (2011)		

Europe			
Long-term exposure value/	Short-term exposure value /	Issuing date	Source
ppm	ppm		
50	100	2009/161	DIRECTIVE 2009/161/EU

DNEL	Target group	Exposure route	Exposure frequency	Source
210 mg/m ³	Workers	Inhalation	Long term effects Local	Company data

Article-No.: GB81002010 Revision Date: 11.03.2022



Replaces version from: 21.09.2018 Print date: 11.03.2022

Version: 2.0/en				
210 mg/m ³	Workers	Inhalation	Long term effects systemic	C
1,5 mg/cm ²	Workers	Skin	Long term effects Local	C

210 mg/m ³	Workers	Inhalation	Long term effects systemic	Company data
1,5 mg/cm ²	Workers	Skin	Long term effects Local	Company data
13,67 mg/kg	Workers	Skin	Long term effects systemic	Company data
105 mg/m ³	Consumers	Inhalation	Long term effects Local	Company data
74,3 mg/m³	Consumers	Inhalation	Long term effects, systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Long term effects Local	Company data
8,2 mg/kg	Consumers	Skin	Long term effects systemic	Company data
1,5 mg/cm ²	Consumers	Skin	Short-term effects Local	Company data

PNEC	Exposure route	Source
0,94 mg/l	freshwater	Company data
0,094 mg/l	marine water	Company data
5,74 mg/kg	sediment	Company data
1,47 mg/kg	Soil	Company data

2-ethylhexyl acrylate

DNEL	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m³	Workers	Inhalation	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Long term effects Local	Company data
0,242 mg/cm ²	Workers	Skin	Short-term effects Local	Company data
4,5 mg/m³	Consumers	Inhalation	Long term effects Local	Company data

PNEC	Exposure route	Source
0,002752 mg/l	fresh water	Company data
0,000272 mg/l	seawater	Company data
2,3 mg/l	wastewater treatment plant	Company data
0,126 mg/kg	sediment Water	Company data
0,126 mg/kg	sediment seawater	Company data
1,0 mg/kg	Soil	Company data
0,0023 mg/kg	Intermittent release.	Company data

1,1'-(p-Tolylimino)dipropan-2-ol

DNEL	Target group	Exposure route	Exposure frequency	Source
2 mg/m³	Workers	Inhalation	Long term effects	Company data
0,6 mg/kg	Workers	Skin	Long term effects	Company data

PNEC	Exposure route	Source
199,5 mg/l	Waste water treatment	Company data
0,0072 mg/kg	marine water	Company data
0,017 mg/l	freshwater	Company data

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en

BAUDER

Replaces version from: 21.09.2018

Print date: 11.03.2022

8.2 Exposure controls

Respiratory protection In interiors and during exceeding of the air limit values carrying of protective

masks is absolutely necessary.

In case of inadequate ventilation wear respiratory protection. Respirator with

filter ABEK-P (brown / gray / yellow / green / white stripes)

Use the indicated respiratory protection if the occupational exposure limit is

exceeded and/or in case of product release (dust).

Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they

must use appropriate certified respirators.

Remarks Recommended Filter type: A1, A2 (in case of higher concentration)

Hand protection Protective gloves complying with EN 374.Please observe the instructions

regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the

product is used, such as the danger of cuts, abrasion, and the contact time.

Unsuitable material woven fabric, Leather gloves

Suitable material Nitrile

Eye protection Safety glasses

Tightly fitting safety goggles

Skin and body protection Wear suitable protective equipment. Long sleeved clothing

General protective and hygiene

measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. Use protective skin cream be-fore handling the product.

Avoid contact with the skin and the eyes.

Engineering measures Ensure adequate ventilation, especially in confined areas. When workers

are facing concentrations above the exposure limit they must use appropriate

certified respirators.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid
Form Liquid

. Colour milky

Odour smell of Methylmethacrylate

pH not applicable

Melting point [°C] / Freezing point[°C] not determined

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en

Replaces version from: 21.09.2018

Print date: 11.03.2022

Boiling point [°C] > 100 °C

10°C Flash point [°C]

Evaporation rate [kg/(s m²)] not determined

Explosion limits [Vol-%] The product itself has not been tested.

methyl methacrylate

Lower limit 1,7 vol. % Upper limit 12,5 vol. %

2-ethylhexyl acrylate

Lower limit 0,9 vol. % Upper limit 6.4 vol. %

Vapour pressure [kPa] not determined Vapour density not determined

Density [g/cm³] 0,98 g/cm³

> 20°C Temperature [°C]

Water solubility [g/l]

Remarks insoluble

Partition coefficient n-octanol /water

(log P O/W)

not determined

Autoignition temperature [°C] not determined Explosive properties Not relevant

In use, may form flammable/explosive vapour-air mixture.

Oxidising properties Not relevant

9.2 Other information

Ignition temperature [°C] not determined

Flow time [s] 55 sec

> Temperature [°C] 20°C

Measuring method DIN cup 6 mm

SECTION 10: Stability and reactivity

10.3 Possibility of hazardous reactions

Hazardous reactions The product is normally supplied in a stabilized form. If the permissible

storage period and/or storage temperature is noticeably exceeded, the product may

polymerize with heat evolution. Risk of receptacle bursting.

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018

Print date: 11.03.2022

10.4 Conditions to avoid

Conditions to avoid Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid Reacts violently with peroxides. Reducing agents, Strong bases, Amines,

Oxidizing agents

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

methyl methacry	/late			
Value	Test criterion	Test species	Measuring method	Source
>5000 mg/kg	LD50	rat	OECD Test Guideline 401	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
4435 mg/kg	LD50	rat	Company data

aliphatic urethanacryl	ate		
Value	Test criterion	Test species	Source
>2001 mg/kg	LD50	rat	Company data

1,1`-(p-Tolylimino)dipropan-2-ol			
Value	Test criterion	Test species	Source
45 mg/kg	LD50	rat	Company data

Dermal toxicity [mg/kg]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
>5000 mg/kg	LD50	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	Company data

1,1`-(p-Tolylimino)dip	ropan-2-ol		
Value	Test criterion	Test species	Source
2001 mg/kg	LD50	rat	Company data

Inhalative toxicity [mg/l]

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

Hazardous ingredients

2-ethylhexyl acrylate		
Value	Test species	Source
1,19 mg/l	rat	Company data

LC50 Inhalation 4h for vapours [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	Company data

Irritant effect on skin

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
irritating	rabbit	Company data

2-ethylhexyl acrylate			
Value	Test species	Exposure duration [h]	Source
Skin irritation	rabbit	4 h	Company data

aliphatic urethanacrylate	
Value	Source
May cause skin irritation.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No skin irritation	Company data

Irritant effect on eyes

methyl methacrylate		
Value	Test species	Source
Irritant	rabbit	Company data

2-ethylhexyl acrylate			
Value	Measuring method	Test species	Source
slightly irritating	OECD Test Guideline 405	rabbit	Company data

aliphatic urethanacrylate	
Value	Source
Causes serious eye irritation.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source

Article-No.: GB81002010 Revision Date: 11.03.2022



Replaces version from: 21.09.2018

Print date: 11.03.2022

Irritant Company dat	ta
----------------------	----

Sensitization

Version: 2.0/en

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
Skin sensitization	mouse	Company data

2-ethylhexyl acrylate	
Value	Source
Skin sensitization	Company data

1,1`-(p-Tolylimino)dipropan-2-ol	
Value	Source
No sensitization responses were observed.	Company data

Carcinogenic effects

Hazardous ingredients

methyl methacrylate		
Value	Test species	Source
not a carcinogen	rat, mouse	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Mutagenicity

Hazardous ingredients

methyl methacrylate	
Value	Source
not mutagenic	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

1,1`-(p-Tolylimino)dipropan-2-ol		
Value	Source	
negative	Company data	

Reproduction toxicity

a_a. a c a c g. c a c c	
methyl methacrylate	
Value	Source
not toxic to reproduction	Company data

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022



Replaces version from: 21.09.2018
Print date: 11.03.2022

Version: 2.0/en

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
Causes respiratory tract irritation.	Company data

2-ethylhexyl acrylate	
Value	Source
Causes respiratory tract irritation.	Company data

Specific target organ toxicity (repeated exposure) [mg/kg]

Hazardous ingredients

methyl methacrylate	
Value	Source
No known effect.	Company data

2-ethylhexyl acrylate	
Value	Source
No known effect.	Company data

11.2 Additional information

Experience in practice Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting. Irritating to eyes, respiratory system and skin. Irritatingto mucous

membranes

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

methyl methacrylate					
Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source
191 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data

2-etnyinexyi	acrylate	

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

Value	Test criterion	Test species	Measuring method	Exposure duration [h]	Source
1,81 mg/l	LC50	On- corhynchus mykiss (rain- bow trout)	OECD Test Guideline203	96 h	Company data

1,1`-(p-Tolylimino)dipropan-2-ol					
Value	Test criterion	Test species	Exposure duration [h]	Source	
17 mg/l	LC50	Brachydanio re- rio (zebra fish)	96 h	Company data	

Toxicity to daphnia [mg/l]

Hazardous ingredients

methyl methacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
69 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data

2-ethylhexyl	2-ethylhexyl acrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
1,3 mg/l	EC50	Daphnia magna (Water flea)	48 h	OECD Test Guideline202	Company data	

aliphatic urethanacry	ylate		
Value	Test criterion	Test species	Source
>100 mg/l	LC50	Daphnia magna (Water flea)	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure duration [h]	Source
28,8 mg/l	EC50	Daphnia magna (Water flea)	18 h	Company data

Toxicity to algae [mg/l]

methyl meth	methyl methacrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source	
>110 mg/l	EC50	Selenastrum capricornu- tum (green algae)	72 h	OECD Test Guideline201	Company data	

Article-No.: GB81002010 Revision Date: 11.03.2022 Version: 2.0/en



Replaces version from: 21.09.2018 Print date: 11.03.2022

2-ethylhexyl acrylate					
Value	Test criterion	Test species	Exposure duration [h]	Measuring method	Source
1,71 mg/l	ErC50	Desmod- esmus sub- spicatus	72 h	OECD Test Guideline201	Company data

1,1`-(p-Tolylimino)dipropan-2-ol				
Value	Test criterion	Test species	Exposure dura- tion [h]	Source
245 mg/l	EC50	Desmodesmus subspicatus	27 h	Company data

NOEC (fish) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
9,4 mg/l	Brachydanio rerio (ze- bra fish)	OECD Test Guideline 210	Company data

NOEC (daphnia) [mg/l]

Hazardous ingredients

methyl methacrylate			
Value	Test species	Measuring method	Source
37 mg/l	Daphnia magna (Water flea)	OECD Test Guideline 202	Company data

NOEC (algae) [mg/l]

Hazardous ingredients

nazaraoao mgroatonto			
2-ethylhexyl acryl	ate		
Value	Test species	Measuring method	Source
0,45 mg/l	Desmodesmus subspi-	OECD Test Guideline	Company data
	catus	201	

12.2 Persistence and degradability

Biodegradability

nazaraoao mgroaionto			
methyl methacrylate			
Value	Method of analysis	Source	
Readily biodegradable.	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	Company data	

2-ethylhexyl acrylate		
Value	Source	
Readily biodegradable.	Company data	

	1,1`-(p-Toly	vlimino)dipro	pan-2-ol
--	--------	--------	---------	--------	----------

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022



Replaces version from: 21.09.2018
Print date: 11.03.2022

Version: 2.0/en	Print date: 11.03.

Value	Source
Poorly biodegradable.	Company data

12.3 Bioaccumulative potential

Bioaccumulation

Hazardous ingredients

methyl methacrylate	
Value	Source
Does not bioaccumulate.	Company data

2-ethylhexyl acrylate	
Value	Source
Bioaccumulation slight, log Pow 4,64	Company data

1,1`-(p-Tolylimino)dipropan-2-ol		
Value	Source	
no data available	Company data	

12.4 Mobility in soil

Mobility

Hazardous ingredients

Tid Edit do do Trigit di citto				
methyl methacrylate				
Mobility	Source			
Terrestrial Compartment Not relevant	Company data			

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

Hazardous ingredients

nazaruous ingreuients				
methyl methacrylate				
Value	Source			
This substance is not considered to be persistent,	Company data			
bioaccumulating nor toxic (PBT).				

2-ethylhexyl acrylate			
Value	Source		
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data		

aliphatic urethanacrylate	
Value	Source
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).	Company data

1,1`-(p-Tolylimino)dipropan-2-ol

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

Value	Source
This substance is not considered to be persistent,	Company data
bioaccumulating nor toxic (PBT).	

12.6 Other adverse effects

Further information on ecology We have no quantitative data concerning the ecological effects of this

product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations According to the European Waste Catalogue, Waste Codes are not product

specific, but application specific. The following Waste Codes are onlysuggestions:

Waste Code 08 01 11* waste paint and varnish containing organic solvents or other

dangerous substances

Uncleaned empty packaging Empty containers should be taken for local recycling or waste disposal.

Dispose of in accordance with local regulations.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.2 Description of the	PAINT	PAINT	PAINT
goods			
UN proper shipping name		PAINT	Paint
14.3 Transport hazard	3	3	3
class(es)			
14.4 Packaging group	III	III	III
Labels	3	3	3
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC

Not relevant

Code

Commercial Product Name: Bauder LiquiPAVE R SO 10KG

Article-No.: GB81002010 Revision Date: 11.03.2022

Version: 2.0/en



Replaces version from: 21.09.2018
Print date: 11.03.2022

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations Additionally, observe any national regulations!

Classification in compliance withthe

Industrial Safety Regulation

highly flammable

GISCODE RMA10

SECTION 16: Other information

Relevant H-phrases H225: Highly flammable liquid and vapour.

H300: Fatal if swallowed. H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Wording of the hazard classes Flam. Liq.: Flammable liquid

STOT SE: Specific target organ toxicity - single exposure

Skin Irrit.: Skin irritation Skin Sens.: Skin sensitization

Aquatic Chronic: Hazardous to the aquatic environment

Eye Irrit.: Serious eye irritation Acute Tox.: Acute toxicity

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Flam. Liq. 2; H225	Calculated
Skin Irrit. 2; H315	Calculated
Skin Sens. 1; H317	Calculated
STOT SE 3; H335	Calculated

Recommended restrictions Reserved for industrial and professional use.

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.