

Bauder PMMA Cleaner

V5 15.07.2024

Product description	Bauder PMMA Cleaner is used with the Bauder LiquiTEC roofing and balcony PMMA products.
Application fields	It is used to pre-treat substrates and to degrease metal when overcoating or if work is interrupted. It can also be used to clean tools.



Article Number GB81007010

Characteristic	Unit	Value
Gross weight	kg	8.85
Pack size	litre	9
Colour		Transparent
Coverage	litre/m ²	0.2 Depending on the degree of soiling and the type of substrate. Consumption based on a smooth non-absorbent surface
Base		ethyl acetate
Drying time at 20°C*	minutes	20 approx.
Overcoat time at 20°C*	minutes	20 to 60 Ensure surface is dry before overcoating
Shelf life unopened	months	12

*Times will be slightly increased at lower temperatures and slightly reduced at higher temperatures.

Storage guidance	The product should be stored in a secure storage area, unopened in a dry condition at a temperature of 5°C to 25°C. Where there are storage containers on site, these may be suitable for storing products. This will ensure the stated shelf-life. The product will have a limited life once the container is opened. The products must not be exposed to a direct naked flame or other ignition sources, or to solvents or other chemicals. All information is provided as a guideline only. Open time and cure time are both dependent on a range of variables: temperature, substrate being bonded, method of application, weight of material applied and relative humidity.	
Packaging material	The product is packaged in tin plate rectangular steel tin with a polypropylene berg closure. Weight of packaging approximately 0.983 kg.	
Handling/PPE	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.	
Emptying and disposal guidance	Empty containers should be taken for local recycling or waste disposal. Dispose of in accordance with local regulations. PMMA Cleaner 07-02-04* - other organic solvents, washing liquids and mother liquors	
Further information/ documents	Current documents such as brochures, installation guides, etc. can be found by visiting www.bauder.co.uk	
International Standards Organisation (ISO)	ISO 9001:2015 Quality Management	Certificates EN1271 and DEKRA 80408283
	ISO 14001:2015 Environmental Management	Certificates A10552 and DEKRA 170408038

Technical data sheet



Installation Guidance

Installation is to be carried out by Bauder Approved Contractors in accordance with the specification and guidelines. Please consult the Bauder technical department.

Substrate assessment / pre-treatment / preparation

Ensure that the substrate is clean, dry, and free from dust, grease, oil, and any other contamination.

The substrate must be assessed, treated, and prepared in accordance with the Bauder project specification.

Application

Where waterproofing and coating work is interrupted for more than 12 hours, the lap must be treated with PMMA Cleaner.

Wearing the appropriate personal protective equipment, pour onto a clean cloth and apply an even layer by wiping the surface to remove any contamination. Regularly replace the cloth. Large areas can be treated by mopping.

Tool Cleaning

Decant the cleaner into a suitable clean receptacle. Clean tools with PMMA Cleaner immediately after use. Merely placing tools in the cleaner will not prevent hardening.

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.

