


Bauder Thermotech Glass Insulation

V6 08.05.2024

Product description	PIR insulation board with a coated glass tissue facing on both sides, available in a uniform thickness or tapered to falls.
Application fields	This product is designed for use with torch-applied, self-adhesive or adhered waterproofing membranes.
Facing	top: Coated glass tissue bottom: Coated glass tissue
Board edge	Square (not rebated)
Board size	Flatboard 25 to 150mm Tapered varies



Characteristic	Test method	Unit	Value
External dimension	EN 822	mm	Flatboard 1200 length x 600 width Tapered 1200 length x 1200 width
Thickness	EN 823	mm	Flatboard = 25 to 150 Tapered varies
Weight		Kg/m ³	32
Reaction to fire	EN 13501 - 1	-	F
Compressive strength (with 10% compression)	EN 826	kPa	≥150
		N/mm ²	0.15
		Kg/m ²	15,000
Thermal conductivity (λ_D) - (EU)	EN 13165	W/mK	Up to 80mm = 0.027 80 to 119mm = 0.025 120 to 150mm = 0.024
Tapered falls available			1:60 & 1:80

Compressive strength for permanently sited loads – please contact Bauder Ltd where plant/equipment is to be sited on top of the Bauder system

Storage/ Transport	Store the materials outdoors with suitable robust UV resistant, flame-retardant tarpaulin. Ensure the product(s) are clear of buildings and any other storage areas. The products must not be exposed to a direct naked flame or other ignition sources, or to solvents or other chemicals. All insulation boards must be kept dry, on pallets and off the ground. The packaging of Bauder Insulation products should not be considered adequate for weather protection. Where there are storage containers on site, these may be suitable for storing products.
Product storage guidance	All insulation boards must be kept dry, on pallets and off the ground. The packaging of Bauder Insulation products should not be considered adequate for outside protection. Ideally boards should be stored inside a building. If outside storage cannot be avoided the boards should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin.
Packaging material	The product will be delivered on EPS skids or wooden pallets with polythene overwrap to protect the product.
Handling/PPE	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using the product, installers should be provided with, and wear, suitable personal protective equipment.
Shelf life	When stored correctly, the product has no stated shelf life.
Disposal guidance	Rigid polyurethane foam waste can be disposed of with household waste or commercial waste similar to household waste (European waste catalogue EWC number 170604 "Insulation material").
Re-use options of product	Please refer to EPD stated below in Certification and environmental information.
Further information/ documents	Current documents such as brochures, installation guides, etc. can be found by visiting www.bauder.co.uk

