## **System summary**



# Liquid applied cold roof covering system - cold applied

# Bauder LiquiBALKON Buried Balcony & Walkway System

Two coat PMMA waterproofing with polyester fleece reinforcement, cold applied liquid balcony and walkway system suitable for new build and refurbishment applications. A granular quartz finish provides a key for bonding tiles.

Function	Product name	Thickness (mm)	Weight (kg/m²)	Ind	dicative
1 Trafficable surface	Tiles on a suitable solvent-free exterior grade cementitious adhesive	Project specific	Project specific		1
Aggregate bond coat	Bauder LiquiBALKON and Bauder Quartz	3	7.5		ıııı
3 Waterproofing	Bauder LiquiBALKON applied in 2 coats, reinforced with 110g Reinforcement Fleece	2	3.11	1 James	
Primer	Varies depending upon substrate type – please refer to specification	nominal	nominal		
System Build-up (excluding tiles an		5	10.61		
In-depth and up-to element within a s	p-date product specific technical da ystem.	ata is available i	for each		
Download from ou	r website bauder.co.uk/technical-o	entre			

### **Characteristics of the system**

- Quick curing polymethylmethacrylate system
- Seamless cold applied liquid.
- UV resistant.
- Solvent, halogen and isocyanate free.
- Comprehensive guarantee packages to meet project requirements.

## **System summary**

### **Accreditations and approvals**





System variations are available to the specifier so that a tailored solution meets the needs of the building. The selection of products should be confirmed with our technical department to ensure suitability for the individual construction requirements of the flat roof.

E: technical@bauder.co.uk

T: 01473 257671

#### **OPTIONS AVAILABLE**

In-depth and up-to-date product specific technical data is available for each component within a system. Download from our website bauder.co.uk/technical-centre

Membrane finish colours
for exposed details if
required.
LiquiDETAIL is Blue Grey (RAL
7031) as standard.
Blue grey
Stone grey
Traffic grey
LiquiBALKON is Pebble Grey
(RAL 7031) RAL 7030
RAL 7043

#### System fire performance

Please contact the Bauder Technical Dept to check if the system assembly stated has an independently tested performance against fire or are deemed to satisfy approval.