## **System summary**




# Liquid applied cold roof covering system - cold applied

## Bauder LiquiBALKON/LiquiPAVE RF Balcony & Walkway System

Two coat PMMA waterproofing with polyester fleece reinforcement, cold applied liquid balcony and walkway system suitable for new build and refurbishment applications. A hard-wearing granular quartz finish provides a trafficable surface.

	Function	Product name	Thickness (mm)	Weight (kg/m²)
1	Aesthetic seal coat	Bauder LiquiFINISH	1	0.65
2	Aggregate bond coat	Bauder LiquiPAVE RF and Bauder Quartz	4	10
3	Waterproofing	Bauder LiquiBALKON applied in 2 coats, reinforced with 110g Reinforcement Fleece	2	3.11
	Primer	Varies depending upon substrate type – please refer to specification	nominal	nominal
System Build-up			7	13.76
In-depth and up-to-date product specific technical data is available for each				



#### **Characteristics of the system**

element within a system.

Quick curing polymethylmethacrylate system

Download from our website bauder.co.uk/technical-centre

- Seamless cold applied liquid.
- UV resistant.
- Solvent, halogen and isocyanate free.
- Comprehensive guarantee packages to meet project requirements.

#### **Accreditations and approvals**



### System summary



System variations are available to the specifier so that a tailored solution meets the needs of the building. The selection of products should be confirmed with our technical department to ensure suitability for the individual construction requirements of the flat roof.

E: technical@bauder.co.uk

T: 01473 257671

#### **OPTIONS AVAILABLE**

In-depth and up-to-date product specific technical data is available for each component within a system. Download from our website bauder.co.uk/technical-centre

Membrane finish colours.
LiquiDETAIL is Blue Grey (RAL
7031) as standard.
LiquiBALKON is Pebble Grey
(RAL 7032) as standard

Blue grey

**RAL 7031** 

Stone grey RAL 7030

Traffic grey RAL 7043

#### System fire performance

Please contact the Bauder Technical Dept to check if the system assembly stated has an independently tested performance against fire or are deemed to satisfy approval.